



DECLARATION OF PERFORMANCE

Product Type Description : TS EN 14411 Dry-Pressed Ceramic Tiles
Purpose of Usage : Indoor Wall Tile
Producer : KARO METRO SERAMİK SANAYİ VE TİCARET A.Ş.
Bozüyük Org. San. Bölgesi 1.Cad. No:1/4
Poyra Köyü / Bozüyük / Bilecik / TURKEY

According to the Regulation (EU) No 305/2011 of the European Parliament and of the Council, the product mentioned above confirms all the requirements of EN 14411 Annex L Group BIII (water absorption $E > 10\%$) standard for ceramic tiles.

Characteristics	Declared Values
Reaction to fire	Class A1fl
Release of dangerous substance, for	
Cadmium	< 0.02 mg/dm ²
Lead	< 0.1 mg/dm ²
Breaking Strength (t=thickness)	> 600 N (t \geq 7,5 mm) > 200 N (t<7,5 mm)
Bond strength-adhesion for	
For cementitious adhesives Type C2	\geq 0,5 N/mm ²
Dispersion adhesive	NPD
Reaction resin adhesive	NPD
Thermal Shock Resistance	Pass
Durability for	
Internal use	Pass

The performance of the product subject to this declaration is in conformity with the declared performance in the table above. This declaration of performance is issued under the sole responsibility of Karo Metro Seramik Sanayi ve Ticaret A.Ş.

Hayati Ulukaya

Production Manager